

1-Port USB 3.0 15m Active Extension Cable

The USB 3.0 Spectra[™] 3001-15 is a 15 meter (49.21 ft) active copper cable that extends a SuperSpeed USB 3.0 device.



Features

Take advantage of USB 3.0's blazing 5Gbps speeds extended 15 meters over active copper cabling. This rugged SuperSpeed cable offers flexibility in extending USB 3.0 devices in commercial and industrial locations such as machine vision cameras, security cameras, and storage drives. Key features include:

- USB 3.0 extension for 15m
- Supports USB 3.0 throughputs up to 5Gbps
- Bus powered from host computer, no external power supply needed
- USB 3.0 device port provides 5V, 900mA power
- Second USB 3.0 power connector for use if additional power is required
- Locking USB connector
- Slots on device port for convenient cable tie mounting
- Rugged grade cabling
- Status LED at device port with power, enumeration and over-current indication
- Works with AIA USB3 Vision[™] compliant devices

Includes the ExtremeUSB[®] suite of features:

- Transparent USB extension
- True plug and play; no software drivers required
- Works with all major operating systems: Windows[®], Mac OS X[®], and Linux[®]

Applications

- Machine vision camera extension
- Post-production editing

- Security camera extension
- Remote storage drives



Specifications subject to change without notification. ©2014 Icron Technologies Corp. #90-01116-A06

(TREME-

Icron

4664 Lougheed Hwy. Suite 221 Burnaby, BC, V5C 5T5, Canada

icron.com +1 604 638 3920

USB 3.0 Spectra[™] 3001-15 Specifications



Locking USB Receptacle



-EXTREME-USB®

Specifications subject to change without notification. ©2014 Icron Technologies Corp. #90-01116-A06

RANGE		
Active Copper Cable:	15m (49.21 ft)	
SPEEDS		
USB 3.0:	Up to 5Gbps (Not backward compatible with USB 2.0/1.1)	
PHYSICAL		
USB Connector on Device Side:	1 x USB 3.0 Type A Locking Receptacle	
USB Connectors on Host Side:	1 x USB 3.0 Type A Host Connector	
	1 x USB 3.0 Type A Power Connector (required for devices drawing more than 2.5W)	
Cable Diameter:	6.9mm (0.27")	
Jacket Material:	PVC	
Bend Radius:	28mm (1.10")	
Mounting Slots on Device Side:	Slots for Cable Tie	
POWER		
Power Source:	Bus Power	
Available Current:	5V, 900mA	
ENVIRONMENTAL		
Operating Temperature:	0°C to 50°C (32°F to 122°F)	
Storage Temperature:	-20°C to 70°C (-4°F to 170°F)	
Operating Humidity:	20% to 80% relative humidity, non-condensing	
Storage Humidity:	10% to 90% relative humidity, non-condensing	
COMPLIANCE		
EMC:	FCC (Class B), CE (Class B)	
Environmental:	RoHS2 (CE)	
Flammability:	VW-1 (UL 1581)	
Machine Vision:	Works with AIA USB3 Vision [™] compliant devices	
SUPPORT		

2 years

Ordering Information

The USB 3.0 Spectra[™] 3001-15 active cable extender solution package includes a 15 meter USB 3.0 Spectra 3001-15 active copper cable, zip tie strap, Quick Start Guide and two-year warranty.

For more information please email sales@icron.com, call +1 604 638 3920 or locate a distributor/reseller in your area by visiting icron.com/where-to-buy.

PART #	NAME	DESCRIPTION
00-00351	USB 3.0 Spectra™ 3001-15	USB 3.0 15m Active Extension Cable

Warranty: